



**Redi-Brite**  
**Industries Pty Ltd**

ABN 55 010 354 140

# Lapping Compound

## Oil Filled

Phone : 61 7 3287 1400

Fax: 61 7 3807 3197

Revision: September 2011

8 Quindus Street Beenleigh Qld 4207 AUSTRALIA

Email : [sales@redibrite.com.au](mailto:sales@redibrite.com.au)

Website: [www.redibrite.com.au](http://www.redibrite.com.au)

## MATERIAL SAFETY DATA SHEET

**Emergency Telephone Number:** Business Hrs. (07) 3287 1400

**Contact – Malcolm Banks:** After Hrs. (07) 5546 4042

### 1. IDENTIFICATION OF PRODUCT

Lapping Compound – Oil Filled

#### **Application**

Lapping Operations.

Not hazardous according to the criteria of Worksafe Australia.

This MSDS consists of 4 pages. Please contact your Redi-Brite representative for any additional copies.

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Chemical Composition**

A blend of severely solvent refined mineral oil, soap thickener, and proprietary performance additives together with synthetic abrasive particles.

#### **Hazardous Components**

No component is present at sufficient concentration to require a hazardous classification.

### 3. HAZARDS IDENTIFICATION

This material is not considered to be hazardous to health, but should be handled in accordance with good industrial hygiene and safety practices.

*Please Note:* High Pressure Applications

Injections through the skin resulting from contact with the product at high pressure constitute a major medical emergency.

See "Medical Advice" under First Aid Measures, Section 4 of this Material Safety Sheet.

### 4. FIRST-AID MEASURES

#### **Eyes**

Flood eyes with plenty of water for 20 minutes. If irritation occurs seek medical advice.

#### **Skin**

Remove contaminated clothing and wash skin thoroughly with soap and water. If irritation persists seek medical advice.

### **Ingestion**

If swallowed, do NOT induce vomiting. Seek medical advice.

### **Inhalation**

Remove affected person from contaminated area and seek medical advice. If he/she is not breathing apply artificial respiration and seek urgent medical advice.

### **Medical Advice**

Treatment should in general be symptomatic and directed to relieving any effects.

Note: High Pressure Applications

Injections through the skin from contact with the product at high pressure constitute a major medical emergency. Injuries may not appear serious at first but within a few hours tissue becomes swollen, discoloured and extremely painful with extensive subcutaneous necrosis. Surgical exploration should be undertaken without delay. Thorough and extensive debridement of the wound and underlying tissue is necessary to reduce tissue loss and prevent or limit permanent damage. Note that high pressure may force the product considerable distances along the tissue planes.

## **5. FIRE-FIGHTING MEASURES**

Use foam, CO<sub>2</sub> or powder.

FIRES IN CONFINED SPACES SHOULD BE DEALT WITH BY TRAINED PERSONNEL WEARING APPROVED BREATHING APPARATUS.

Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over.

### **Combustion Products**

Will not burn unless pre-heated. Toxic fumes may be evolved on burning or exposure to heat.

See stability and Reactivity, Section 10 of this Material Safety Data Sheet.

## **6. ACCIDENTAL RELEASE MEASURES**

Remove all sources of ignition and prevent further leakage if safe to do so. Scoop up excess material and place in suitable labeled sealed containers for disposal according to local and state authority regulations and guidelines. Clean the contaminated area with water and detergent. Do not allow this product to enter drains, sewers or water courses - inform the local authorities if this occurs.

## **7. HANDLING AND STORAGE**

### **Handling Precautions**

Avoid contact with skin and eyes, and avoid breathing vapours or mists. When exposure is likely, personal protective equipment such as safety glasses, PVC gloves, PVC apron and sleeves and PVC or rubber boots.

Where the concentration of vapour or mist is expected to approach the exposure limit, goggles and correct respiratory protection should be worn (Note: If the vapour/mist concentrations exceed the exposure limit by more than 10 times, air supplied apparatus should be worn). For prolonged elevated exposures a full face air supplied or self contained breathing apparatus should be worn.

If contamination occurs, change clothing and discard internally contaminated gloves and footwear. Launder contaminated clothing before reuse.

### **Fire Prevention**

Keep storage tanks, pipelines, fire exposed surfaces etc. cool with water spray. Shut off any leak if safe to do so and remove sources of re-ignition.

### **Storage Conditions**

Store in a well ventilated area away from ignition sources, oxidizing agents foodstuffs and clothing. Keep containers closed when not in use.

## **8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

### Exposure Limits

Ensure good ventilation. Avoid, as far as reasonably practicable, inhalation of vapour, mists or fumes generated during use. If vapour, mists or fumes are generated, their concentration in the workplace air should be controlled to the lowest reasonably practicable level. Worksafe Australia recommends an exposure standard of 5 mg/m<sup>3</sup> (oil mist) for an 8 hour time weighted average (TWA). Short term exposure limit (STEL) 10mg/m<sup>3</sup> (oil mist).

### Protective Clothing

Wear face visor or goggles in circumstances where eye contact can accidentally occur. Change heavily contaminated clothing as soon as reasonably practicable and launder before re-use. Wash any contaminated underlying skin with soap and water.

If skin contact is likely, wear impervious protective clothing and/or gloves.

### Respiratory Protection

Respiratory protection is unnecessary, provided the concentration of vapour, mists or fumes is adequately controlled.

The use of respiratory equipment must be strictly in accordance with the manufacturers' requirements governing its selection and use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### Typical Values

Grades: H120, H180, H240, H320, H500, H700

	Test Method	Units	
Physical state			greasy grit
Colour			brown
Odour			oily
Density @ 15 degrees Celcius	ASTM D 1298	kg/L	0.91
Flash Point (PMC)	ASTM D 93	deg C	>228

## 10. STABILITY AND REACTIVITY

### Conditions to Avoid

Products of this type are stable and unlikely to react in a hazardous manner under normal conditions of use.

Hazardous polymerisation reactions will not occur.

This material is combustible.

### Materials to Avoid

Avoid contact with strong oxidizing agents foodstuffs, ignition sources and clothing.

### Hazardous Decomposition Products

Thermal decomposition can produce a variety of compounds, the precise nature of which will depend on the decomposition conditions.

Incomplete combustion/thermal decomposition will generate smoke, carbon dioxide and hazardous gases, which will include carbon monoxide.

## 11. TOXICOLOGICAL INFORMATION

### Eyes

Product may cause slight to moderate irritation to the eyes.

### Skin

Mildly irritating to skin. Prolonged and repeated skin contact may cause dermatitis due to defatting effect.

### Ingestion

Slightly toxic, may cause gastric irritation.

### Inhalation

Inhalation of the vapours (generated at elevated temperatures) or mists can cause irritation to the nose and throat.

## 12. ECOLOGICAL INFORMATION

### **Mobility**

Spillages are unlikely to penetrate the soil.

### **Persistence and degradability**

The oily segment of the product is inherently biodegradable.

The abrasive grain particles suspended within are not biodegradable.

### **Bioaccumulative potential**

There is no evidence to suggest bioaccumulation will occur.

### **Aquatic toxicity**

May be harmful to aquatic organisms. Oxygen transfer could also be impaired.

## 13. DISPOSAL CONSIDERATIONS

Dispose of via an authorised person/licensed waste disposal contractor in accordance with local regulations.

Incineration may be carried out under controlled conditions provided that local regulations for emissions are met.

Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil.

## 14. TRANSPORT INFORMATION

Not classified as hazardous for transport (ADG, UN, IATA/ICAO).

Classified as a Combustible Liquid C2, AS 1940-1993

## 15. REGULATORY INFORMATION

Not classified as a hazardous substance using the Workplace Australia criteria.

Not classified using the criteria in the Standard Uniform Schedule for Drugs and Poisons.

## 16. OTHER INFORMATION

### **Compiled by:**

Redi-Brite Industries Pty. Ltd.

ABN 55 010 354 140

The information contained herein is based on data considered accurate available at this date. The data herein relates only to the specific material designated in this material safety data sheet and does not relate to use in combination with any other material or in any process. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Redi-Brite Industries Pty. Ltd. assumes no responsibility for personal injury or property damage to vendees, users or third parties caused by the material. Such vendees or users assumes all risks associated with the use of the material.

This data sheet and the health, safety and environmental information it contains is considered to be accurate as of the date specified below. We have reviewed any information contained herein which we received from sources outside Redi-Brite Industries Pty. Ltd. However, again, no warranty or representation, expressed or implied is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. No statement made in this data sheet shall be construed as a permission, recommendation or authorization given or implied to practise any patented invention without a valid licence. Redi-Brite Industries Pty. Ltd. shall not be responsible for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.

*Please Note: Material Safety Data Sheets (MSDS) can be found on our website at [www.redibrite.com.au](http://www.redibrite.com.au)*